PK0933

Light Pole Kit with Three LED Area Lights, Selectable Wattage 80/100/120/150 & Color Temperature, 10-25 Foot Pole Height Options

	3	
, <u> </u>		
oravil	:albt I	

		L	10-23 1	oot Pole He	agrit Options	Energy Light LLC
iite:	State:			Client Name:		
tes:				Approvals:		Date:
Square steel ligh and hardware, so Light Pole: Pole Shaft: 4 inc commercial grad Pole Height: Opt Custom heights: A Anchor Bolts: A Each anchor bolt Bolt Circle: 8-1/2 Handhole: Handhole: Handhole: Handhole: Dark Bron Base Cover: ABS Warranty: 1 Yea	s Plastic base cover v or num construction wi o maximize heat diss nze.	this complete with indicate a base cover. 10 ft., 15 ft. and 20 im yield strength of the ft., 15 ft., 20ft. and iteel anchor bolts is the same as the	ft.) and 7 gauge (25 55,000 psi 25 ft. provided.	(Opt	LED Fixture Top View LED Fixture Bottom View	(3)Direct Mounting Brackets
Preset Color Ten Light Distributio Type 4 and Type Photocell: Photo Dimming: 0-10V Dimming contro	rs: 3000K; 4000K; 50 mperature: 5000K. on: Type 3 standard. e 5 options as special ocell is optional. I Dimming Capable. I not provided (field sted for Wet Locatio Premium. ft²	il order. install). ns.	4 Slots [—] 90 °Apart Bolt Circle: 8.5" —	10.5 "SQ. Base Plate	Handhole Cover	Pole Heigh
				1	2-Piece Base Cover	18" Base Plate
POWER (W)	80	100	120	150		I I
AMPS	0.74x3=2.22 @ 120V/ 0.33x3=0.99 @ 277V	0.93x3=2.79 @ 120V/ 0.40x3=1.20 @ 277V	1.11x3=3.33 @ 120V/ 0.48x3=1.44 @ 277V	1.39x3=4.17 @ 120V/ 0.60x3=1.80 @ 277V	3.75"	
						Pole Anchor
LUMENS/WATT		10	DU			Height Bolt