PK0934

Light Pole Kit with Four LED Area Lights, Selectable Wattage 80/100/120/150 & Color Temperature, 10-25 Foot Pole Height Options

	3	
, <u> </u>		
oravil	:albt I	

State:			Client Name:		
		,			
			_ Approvals:		Date:
square 11 gauge (1 steel with minimur on al heights are 10 re also available et of 4 galvanized st includes 2 nuts and (Bolt Circle range: ole is located 18" al indhole cover is include el also available et of 4 galvanized st includes 2 nuts and (Bolt Circle range: ole is located 18" al indhole cover is include el also available el also available el available el available el available el available el is optional. Dimming Capable. Inot provided (field in steel also el available el a	ts complete with m d a base cover. 0 ft., 15 ft. and 20 m yield strength of ft., 15 ft., 20ft. and teel anchor bolts is 2 washers. 8"-11"). bove the base plate uded. with rivets. th ipation.	ft.) and 7 gauge (25 f 55,000 psi 125 ft. provided. 11.3"	(Opt	LED Fixture Top View Handhole Cover75	(4)Direct Mounting Brackets Pole Height
90	100	120	150	Base Cover	18" / Base Plate
120V/ 0.33x4=1.32 @ 277V	120V/ 0.40x4=1.60 @ 277V	1.11x4-4.44 @ 120V/ 0.48x4=1.92 @ 277V	1.59x4=5.36 @ 120V/ 0.60x4=2.4 @ 277V	3.75" Bolt Project	
	10	60			Pole Anchor Height Bolt
12,800x4=51,200	16,000x4=64,000	19,200x4=76,800	24,000x4=96,000		10 ft, 15 ft, 20 ft
	pole, Four LED light of anchor bolts and square 11 gauge (1 steel with minimum pole of the steel with minimum pole also available at of 4 galvanized standudes 2 nuts and (Bolt Circle range: ole is located 18" all odhole cover is included and the cover is included and the cover with maximize heat dissible. District Watts Volt standard. 3000K; 4000K; 500 Derature: 5000K. Type 3 standard. Soptions as special ell is optional. Dimming Capable. Type 3 standard. Soptions as special ell is optional. Dimming Capable. Type 3 tandard. Type 4 tandard.	pole, Four LED lights complete with more of anchor bolts and a base cover. square 11 gauge (10 ft., 15 ft. and 20 steel with minimum yield strength of boal heights are 10 ft., 15 ft., 20ft. and e also available et of 4 galvanized steel anchor bolts is includes 2 nuts and 2 washers. (Bolt Circle range: 8"-11"). Dole is located 18" above the base plate of the boase cover with rivets. Immonstruction with maximize heat dissipation. E. Dowatts Volt standard. 3000K; 4000K; 5000K Derature: 5000K. Type 3 standard. Soptions as special order. Bell is optional. Dimming Capable. Both provided (field install). Bed for Wet Locations. Temium. Boundard: Boundard:	pole, Four LED lights complete with mounting bracket of anchor bolts and a base cover. square 11 gauge (10 ft., 15 ft. and 20 ft.) and 7 gauge (25 ft steel with minimum yield strength of 55,000 psi onal heights are 10 ft., 15 ft., 20ft. and 25 ft. e also available at of 4 galvanized steel anchor bolts is provided. Includes 2 nuts and 2 washers. (Bolt Circle range: 8"-11"). Dole is located 18" above the base plate. Include cover is included. e lastic base cover with rivets. Imm construction with maximize heat dissipation. e. Diwatts Volt standard. 3000K; 4000K; 5000K Derature: 5000K. Type 3 standard. Dimming Capable. Doptions as special order. elli is optional. Dimming Capable. Doptions as special order. elli soptional. Dimming Capable. Doptional (field install). Def for Wet Locations. remium. 4 Slots 90°Apart 4 Slots 90°Apart 4 Slots 90°Apart 4 Slots 90°Apart 6 Dimmable 100 120 0.74x4=2.96 @ 0.93x4=3.72 @ 1.11x4=4.44 @ 1.20V/ 0.33x4=1.32 @ 2.77V 2.77V 160 12,800x4=51,200 16,000x4=64,000 19,200x4=76,800	pole, Four LED lights complete with mounting bracket of anchor bolts and a base cover. square 11 gauge (10 ft., 15 ft. and 20 ft.) and 7 gauge (25 ft.) steel with minimum yield strength of 55,000 psi onal heights are 10 ft., 15 ft., 20ft. and 25 ft. e also available to for 4 galvanized steel anchor bolts is provided. Includes 2 nuts and 2 washers. (Bolt Circle range: 8"-11"). pole is located 18" above the base plate. Included to ever is included. Plastic base cover with rivets. Diwatts Volt standard. 3000K; 4000K; 5000K Dimming Capable. Into provided (field install). ed for Wet Locations. remium. Bolt Circle: 8.5" A Slott 90 "Apart A Slott 90 "Apart Base Plate 80 100 120 150 0.74x4=2.96 @ 0.93x4=3.72 @ 1.11x4=4.44 @ 1.39x4=5.56 @ 120V/ 0.33x4=1.32 @ 0.40x4=1.60 @ 0.48x4=1.92 @ 277V 160	pole, Four LED lights complete with mounting bracket of anchor bolts and a base cover. square 11 gauge (10 ft., 15 ft., and 20 ft.) and 7 gauge (25 ft.) steel with minum yield strength of 55,000 psi mal heights are 10 ft., 15 ft., 20ft. and 25 ft. e also available to 16 ft. galvarized steel anchor bolts is provided. Includes 2 nuts and 2 washers. (Bolt Circle range: 8" 1"1"). Be is located 18" above the base plate. Includes 2 nuts and 2 washers. (Bolt Circle range: 8" above the base plate. Included. 20.3 and 10 light included. I